

Optional Lowering System

Install Roller

- Optional unit available to assist with hose installation
- Durable steel construction
- Safety pins hold roller bar in place when not raising/lowering hose
- Available in two sizes depending on hose size



Coupling Diameter		Mounting Roller Part Number	Dimensions
(in)	(mm)		
1 1/4	32	C654110C	29.5 x 16.5 x 15.7 inch 750 x 420 x 400 mm
1 1/2	40		
2	52		
3	76		
4	102		
5	127	C654100C	59 x 33 x 31.5 inch 1500 x 840 x 800 mm
6	152		
8	203		



1. After attaching the pump and power cable, install clamp is then attached. (Making sure the cable is outside).

Install Clamp

- Optional clamp used to raise or stabilize hose during initial installation.



Coupling Diameter		Mounting Clamps Set Part Number
(in)	(mm)	
1 1/4	32	C654310
1 1/2	40	
2	52	
3	76	C654320
4	102	
5	127	C654320
6	152	C654315
8	203	C654315



2. The install clamp is then used to lower the pump during initial installation.



3. After initial installation, pump is lowered into well by use of a vehicle, with a single hose reaching depths up to 990 ft.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.