



KSPA™ Series “Spa Hose” PVC Suction Hose



GENERAL APPLICATIONS

- Commonly referred to as “Flex Pipe”
- Drain Lines
- Spa, Pool, and Hot Tub plumbing

CONSTRUCTION

- PVC Tube with Rigid PVC Helix.
- Laser etched layline.
- Direction of Flow Arrow.

SERVICE TEMPERATURE RANGE

-4°F (-20°C) to +150°F (+65°C)*

*Actual service temperature range is application dependent.

FEATURES AND ADVANTAGES

- Designed to be glued into Schedule 40 PVC fittings.
- Meets IAPMO criteria.

EASY INSTALLATION

- Ideal for working in confined areas.
- Permits installers to make smooth, tight turns.
- Requires fewer fittings than rigid pipe when plumbing a normal spa or hot tub application.

VIEW ONLINE



SCAN FOR INFO
or visit
KOA.link/KSPA



Series Number	IPS Size (in)	OD (in)	OD (mm)	Working Pressure at 68°F (psi)	Working Pressure at 104°F (psi)	Vacuum Hg at 68°F (in)	Vacuum Hg at 104°F (in)	Min. Bending Radius at 68°F (in)	Standard Length (ft)	Weight (lbs/ft)
KSPA0-24	1-1/2	1.904	48.36	70	50	28	24	4	100/50	0.44
KSPA0-32	2	2.381	60.48	70	50	28	24	6	100/50	0.58

NOTES:

- Use with recommended primers and PVC cements; consult with glue supplier for recommendations.
- Coils of Kuri Tec® Spa Hose should not be stacked more than five coils high. Hose which has been stacked high may be damaged over time.

PRODUCT WARNING:

- Like other materials, Spa Hoses can be damaged by rodents or insects, including termites. Our warranty does not cover damages caused by them. Spa Hose should not be used underground in areas infested by termites. This product warning shall be given to every purchaser of Spa Hose. (Rev. 7/98)

⚠ WARNING

This product can expose you to DINP, which is known to the State of California to cause cancer or birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.