



SLITHER® SLLDRH-MF Series
3,000 PSI

CONSTRUCTION
A yellow seamless polyolefin tube, double high tensile synthetic fiber braid reinforcement, and abrasion resistant Slither® yellow polyether-urethane cover.
*Male x Female ends for easy connection.

SERVICE TEMPERATURE RANGE
-40°F (-40°C) to +150°F (+66°C)

View Up To Date Info



◀ SCAN OR VISIT
**KOA.link/
SLLDRH-MF**



Series Number	ID (in)	Length (ft)	Hose Color	Max. Working Pressure		Min. Burst Pressure		Min. Bend Radius (inches)	Weight (lbs/ft)
				(psi)	(bar)	(psi)	(bar)		
SLLDRH-MF12x10	3/4	10	Slither Yellow	3,000	206.8	7,500	517.1	5	0.29
SLLDRH-MF12x15	3/4	15	Slither Yellow	3,000	206.8	7,500	517.1	5	0.29
SLLDRH-MF12x20	3/4	20	Slither Yellow	3,000	206.8	7,500	517.1	5	0.29
SLLDRH-MF16x10	1	10	Slither Yellow	3,000	206.8	7,500	517.1	8	0.41
SLLDRH-MF16x15	1	15	Slither Yellow	3,000	206.8	7,500	517.1	8	0.41
SLLDRH-MF16x20	1	20	Slither Yellow	3,000	206.8	7,500	517.1	8	0.41

Get in front with Piranha Leader Hose with a **high visibility cover** for safety



Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.