

WARNING!

IF YOU SEE “IT” – STOP “IT”

FAILURE TO PROPERLY REPAIR OR REPLACE HOSE AFTER EXPOSING WHITE BRAID REINFORCEMENT LAYER CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.

Like strands in a bridge cable, each reinforcement fiber plays an exact role in the ultimate burst strength of the hose.

A **minor** slice or nick in the reinforcement can result in total hose failure.

The age of the hose **does not matter**! It is unfortunate, but even a hose used only one time can be damaged in severe applications.

These hoses must be immediately removed from service.



⚠ DANGER ⚠

READ AND UNDERSTAND THE FOLLOWING

1. NEVER EXCEED THE MAXIMUM WORKING **PRESSURE**.
2. NEVER EXCEED THE MAXIMUM WORKING **TEMPERATURE**.
3. NEVER APPLY PRESSURE TO A **DAMAGED** HOSE.
4. HIGH PRESSURE HOSES ARE DESIGNED TO USE SPECIFIC **FITTINGS** AND **TOOLING**. NEVER USE A DIFFERENT **BRAND** OF FITTINGS OR TOOLING. FAILURE TO DO SO CAN CAUSE DEATH, PERSONAL INJURY AND/OR PROPERTY DAMAGE.
5. A **KINKED**, **CRUSHED**, OR **BLISTERED** HOSE WILL EVENTUALLY FAIL – DO NOT RISK INJURY. IMMEDIATELY REPAIR OR REMOVE HOSE FROM SERVICE.
6. FOLLOW THE PUMP/EQUIPMENT MANUFACTURER'S **INSTRUCTIONS** FOR PRESSURIZED HOSE TESTING.

⚠ Warning: This product can expose you to chemicals, including lead or titanium dioxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65warnings.ca.gov.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

Quality Assurance

FOR YOUR SAFETY THIS REEL OF *PIRANHA* SEWER CLEANING HOSE HAS BEEN FACTORY TESTED AT 150% OF RATED WORKING PRESSURE.

Warning

HOSE INSPECTION:

Hose should be inspected frequently for any signs of cover wear or damage.

HOSE REPAIR/REPLACEMENT:

Hose should be repaired/replaced at the first indication of being kinked, the cover being torn or sliced, or the braid reinforcement being exposed.



PIRANHA HOSE PRODUCTS

End Fittings/Menders/Assembly Tooling



End fittings, menders and assembly tooling for thermoplastic hoses are not interchangeable. It is essential that hose, end fittings, menders and assembly tooling be properly matched. Identification and matching of Piranha Hose Products is simple: The inner tube of all Piranha Sewer Cleaning Hose is YELLOW. (Piranha Hose Products has been assigned this manufacturer's identification code for the hose tube by the Waste Equipment Technology Association.) To assure proper matching of all components, the hose inner tube material, end fittings, menders, and tooling MUST BE COLOR CODED YELLOW.

While there may be several sources for end fittings, menders and assembly tooling that bear the yellow color coding, for safety and reliability - only Piranha factory-tested end fittings, menders and assembly tooling are certified for use with Piranha Hose. The use of end fittings, menders and assembly tooling other than those certified by Piranha Hose Products is at the risk of users. A Piranha certified swaging machine is required for the installation of end fittings and menders. All assembly tooling is designed and produced to be compatible with Piranha Hose Products certified swaging machines.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.