



View Up To Date Info



< SCAN OR VISIT
**KOA.link/
 PF267**



COMPLIANCE DETAILS

Compliances	Size
ANSI 92.2†	1/8" – 1/2"
REACH	All sizes
SAE 100R7	All sizes
SAE J517	All sizes

† For vehicle mounted aerial devices

APPROVED FITTINGS*

- P Series One-Piece Carbon Steel
- P Series One-Piece Stainless
- A Series Two-Piece (PFR ferrule)

*Dependent on hose size

PACKAGING

- Boxed 250' reels or boxed 50' coils
- No more than two pieces per 250' reel. No piece less than 50'

PF267 Series / PF267NC Series

SAE 100R7 Hydraulic Hose (ANSI A92.2) with
 Kink Resistant Technology

GENERAL APPLICATIONS

- Industrial equipment and vehicles (construction, agriculture, material handling, etc.)
- Aerial equipment (PF267NC only)
- Hydraulic oil and lubrication lines

CONSTRUCTION

Tube – Copolyester

Reinforcement – Braided high tensile strength
 fibers

Cover – Abrasion resistant polyurethane. Available with conductive
 black pin pricked cover (PF267), or non-conductive “NC”, orange cover
 (PF267NC series).


SERVICE TEMPERATURE RANGE

-65°F (-54°C) to +200°F (+93°C) for petroleum based hydraulic fluids

*Maximum 140°F (+60°C) for water and phosphate-ester based hydraulic fluids

FEATURES AND ADVANTAGES

- **Kink Resistant Technology** – Proprietary design shown to exhibit 53% better resistance to kink initiation, and 16% less force to bend, versus competitive 100R7 hose in comparison testing.
- **Abrasion Resistant** – Polyurethane cover outlasts rubber versions in applications where the hose rubs against abrasive surfaces.
- **Low Temperature Flex** – Designed to flex at temperatures as low as -65°F; well suited for cold storage applications.
- **Meets ANSI A92.2 (PF267NC Series Only)** – Meets ANSI insulating requirement for aerial devices used in areas of high electricity. Tested to less than 50 microamperes leakage when subjected to 75,000 volts/ft. for 5 min.
- **Pin Pricked Cover (PF267 Series Only)** – Allows trapped gases to escape when necessary, reducing the risk of cover blistering.



Series Number	Size Code	ID		OD		Max. Working Pressure (psi)		Min. Bending Radius		Weight (lbs/ft)	Coupling Recommendations		
		(in)	(mm)	(in)	(mm)	SAE (SF: 4:1)	ANSI (SF: 3:1)	(in)	(mm)		One-Piece	Two-Piece	
PF267/PF267NC	03	3/16	4.8	0.415	10.5	3000	3000	0.75	19	0.05	-	P-03XX-XXX-SS	PFR-03
PF267/PF267NC	04	1/4	6.4	0.496	12.6	2750	3000	1.50	38	0.07	P-04XX-XXX	P-04XX-XXX-SS	PFR-04
PF267/PF267NC	05	5/16	8.1	0.580	14.7	2500	3000	1.75	44	0.09	P-05XX-XXX	-	PFR7-05
PF267/PF267NC	06	3/8	9.7	0.651	16.5	2250	3000	2.00	51	0.12	P-06XX-XXX	-	PFR-06
PF267/PF267NC	08	1/2	13.1	0.834	21.2	2000	3000	3.00	76	0.17	P-08XX-XXX	-	PFR-08
PF267/PF267NC	12	3/4	19.1	1.050	26.7	1250	-	6.00	152	0.24	-	-	PFR-12
Non-stocked size below. Minimum order quantity applies. Contact Kuriyama Customer Service for details.													
PF267/PF267NC	02	1/8	3.2	0.322	8.18	3000	3000	0.75	19	0.04	P-02XX-XXX	-	-
PF267/PF267NC	16	1	25.4	1.360	34.5	1000	-	8.00	203	0.31	-	-	AFX-16

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.