

## Female Socket x Male NPT (Type B)

*(Includes Buna Gasket)*

### Nominal Specifications

Part Number	Size (in)	Working Pressure (psi)	Weight Each (lbs)	Standard Carton
SLB-FP200	2	290	0.97	1
SLB-FP300	3	290	1.78	1
SLB-FP400	4	217	3.59	1
SLB-FP600	6	175	7.12	1
SLB-FP800	8	175	13.57	1



## Male Ball x Male NPT (Type B)

*(Includes Locking Lever Ring)*

### Nominal Specifications

Part Number	Size (in)	Working Pressure (psi)	Weight Each (lbs)	Standard Carton
SLB-MP200	2	290	3.04	1
SLB-MP300	3	290	6.18	1
SLB-MP400	4	217	10.62	1
SLB-MP600	6	175	22.61	1
SLB-MP800	8	175	38.18	1



## Male Ball Plug (Type B)

*(Includes Locking Lever Ring)\**

### Nominal Specifications

Part Number	Size (in)	Working Pressure (psi)	Weight Each (lbs)	Standard Carton
SLB-MPLG200	2	290	1.52	1
SLB-MPLG300	3	290	2.98	1
SLB-MPLG400	4	217	6.33	1
SLB-MPLG600	6	175	12.66	1
SLB-MPLG800	8	175	19.88	1
SLB-MPLG1200	12	175	48.72	1



\* 12" size includes Locking Ring, requires Lever Assist Bar (Type A) to couple (SLA-LV) page 14.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.