




## Tiger™ Pink TPINK™ Series EPDM Septic Suction Hose

### GENERAL APPLICATIONS

- Agriculture liquid fertilizers
- Irrigation lines
- Liquid manure handling
- Marine bilge discharge
- Pumps, rental and construction dewatering
- Pumps, trash
- Septic and wastewater handling
- Used frack solution removal
- Water suction – standard duty

### CONSTRUCTION

EPDM tube with polyethylene helix

### SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +160°F (+71°C)\*

View Up To Date Info



◀ SCAN OR VISIT  
[KOA.link/  
TPINK](https://koya.link/TPINK)



| Series Number | ID   |       | OD   |       | Working Pressure (psi) |          | Vacuum Rating Hg (in) |          | Min. Bending Radius (in) at 68°F | Standard Length (ft) | Weight (lbs/ft) |
|---------------|------|-------|------|-------|------------------------|----------|-----------------------|----------|----------------------------------|----------------------|-----------------|
|               | (in) | (mm)  | (in) | (mm)  | at 68°F                | at 104°F | at 68°F               | at 104°F |                                  |                      |                 |
| TPINK200x100  | 2    | 50.8  | 2.51 | 63.8  | 50                     | 35       | FULL                  | 28       | 5                                | 100                  | 0.67            |
| TPINK300x100  | 3    | 76.2  | 3.60 | 91.5  | 45                     | 30       | FULL                  | 26       | 7                                | 100                  | 1.14            |
| TPINK400x100  | 4    | 101.6 | 4.70 | 119.5 | 40                     | 25       | FULL                  | 26       | 11 1/2                           | 100                  | 1.84            |




## QBEE™ Series Polyethylene Portable Toilet Hose

### GENERAL APPLICATIONS

- Pumps, rental and construction dewatering
- Pumps, trash
- Septic and wastewater handling
- Water suction

### CONSTRUCTION

Flexible polyethylene (LDPE) tube with polyethylene (LDPE) ribs and cuffed ends

### SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +150°F (+65°C)\*



| Part Number | ID   |      | OD   |      | Working Pressure at 68°F (psi) | Vacuum Rating Hg at 68°F (in) | Min. Bending Radius at 68°F (in) | Standard Length (ft) | Weight (lbs/ft) |
|-------------|------|------|------|------|--------------------------------|-------------------------------|----------------------------------|----------------------|-----------------|
|             | (in) | (mm) | (in) | (mm) |                                |                               |                                  |                      |                 |
| QBEE200X30  | 2    | 52.7 | 2.76 | 69.5 | 15                             | 29                            | 3.5                              | 30                   | 0.72            |
| QBEE200X50  | 2    | 52.7 | 2.76 | 69.5 | 15                             | 29                            | 3.5                              | 50                   | 0.72            |

**NOTE:** Service life may vary depending on operating conditions and type of material being conveyed.

\* Actual service temperature range is application dependent.

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.