



MILK™ Series

Food Grade, PVC, Liquid Suction Hose

- GENERAL APPLICATIONS
- Food grade liquids such as milk, beer, wine and juice
 - Ice transfer
 - Milk and dairy product transfer

CONSTRUCTION

PVC tube with rigid PVC helix

SERVICE TEMPERATURE RANGE

-4°F (-20°C) to +150°F (+65°C)*

**Actual service temperature range is application dependent.*

View Up To Date Info



◀ SCAN OR VISIT
**KOA.link/
MILK**



FEATURES AND ADVANTAGES

- **Precision Controlled ID and OD Dimensions** – Facilitates insertion of sanitary fittings.
 - **Food Grade Materials** – Hose complies with applicable FDA⁽⁰³⁾ and 3-A⁽⁰¹⁾ requirements. Hose complies with applicable USDA⁽¹²⁾ requirements.
- **Transparent Construction** – “See-the-flow.” Allows for visual confirmation of material flow.
 - **Smooth Outer Cover** – Provides increased pressure rating and smooth surface for banding.

Series Number	ID		OD		Working Pressure (psi)		Vacuum Rating Hg (in)		Min. Bending Radius (in)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	at 68°F	at 104°F	at 68°F	at 104°F	at 68°F		
MILK150	1 1/2	38.1	1.79	45.5	75	50	Full	26	4	100	0.45
MILK200	2	50.8	2.33	59.2	75	50	28	25	6	100	0.63
MILK250	2 1/2	63.5	2.87	73.0	55	40	28	24	10	100	0.81
MILK300	3	76.2	3.42	86.9	55	40	28	24	11	100	1.18

NOTES:

• Service life may vary depending on operating conditions and type of material being conveyed.

COMPLIANCES (for details see page 87)

3A (01), BSE/TSE (02), FDA (03), Phthalate Free (10), RoHS (11), USDA (12)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.