



Ground Cover GC-C™ Series

Heavy-Duty, Polyurethane Lined, Material Handling Hose

GENERAL APPLICATIONS

- Material handling – heavy duty abrasive
- Mulch, bark, wood chips and other surfacing material delivery
- Soil, seed and compost delivery

CONSTRUCTION

PVC cover with polyurethane liner and rigid PVC helix

SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +150°F (+65°C)*

**Actual service temperature range is application dependent.*

View Up To Date Info



◀ SCAN OR VISIT
**KOA.link/
GC-C**



FEATURES AND ADVANTAGES

- **Abrasion Resistant Polyurethane Liner** – Designed for dry applications where severe abrasion is a factor. Provides longer hose life and lower operating costs versus rubber or PVC hoses.
- **“Cold-Flex” Materials** – Hose remains flexible in sub-zero temperatures.
- **Transparent Construction** – “See-the-flow.” Allows for visual confirmation of material flow.
- **Convolutd Outer Cover** – Provides increased hose flexibility. Allows for easier unwinding and winding on hose reels.
- **Oil Resistant Polyurethane Liner** – Resists most animal and petroleum based oils.

Series Number	ID		OD		Working Pressure (psi)		Vacuum Rating Hg (in)		Min. Bending Radius (in)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	at 68°F	at 104°F	at 68°F	at 104°F	at 68°F		
GC-C400	4	101.6	4.59	116.6	30	15	28	25	6	100	1.00
GC-C500	5	127.0	5.57	141.5	30	15	25	20	10	100	1.80

NOTES:

- Service life may vary depending on operating conditions and type of material being conveyed.

COMPLIANCES (for details see page 87)

Phthalate Free (10), **RoHS** (11)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.