



# MULCH-LT™ Series

Heavy-Duty, Low Temperature, PVC, Material Handling Hose

GENERAL APPLICATIONS

- Material handling – standard duty
- Soil, seed and compost delivery
- Mulch, bark, wood chips and other surfacing material delivery

CONSTRUCTION

PVC tube and rigid PVC helix

SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +150°F (+65°C)\*

*\*Actual service temperature range is application dependent.*

View Up To Date Info



◀ SCAN OR VISIT  
**KOA.link/  
MULCH-LT**



FEATURES AND ADVANTAGES

- **Abrasion Resistant PVC Tube** – Formulated from highly durable PVC compounds for increased abrasion and tear resistance versus standard PVC hoses.
- **“Cold-Flex” Materials** – Hose remains flexible in sub-zero temperatures.
- **Transparent Construction** – “See-the-flow.” Allows for visual confirmation of material flow.
- **Convuluted Outer Cover** – Provides increased hose flexibility.

Series Number	ID		OD		Working Pressure (psi)		Vacuum Rating Hg (in)		Min. Bending Radius (in)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	at 68°F	at 104°F	at 68°F	at 104°F	at 68°F		
MULCH-LT400	4	101.6	4.57	116.0	35	15	Full	28	8	200/100	1.35

NOTES:

- Service life may vary depending on operating conditions and type of material being conveyed.

COMPLIANCES (for details see page 87)

**Phthalate Free** (10), **RoHS** (11)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.