



GTG™ Series

PVC Ducting/Light Material Handling Hose

GENERAL APPLICATIONS

- Cable protection
- Drain lines
- Ducting, ventilation and fume removal
- Dust collection
- Material handling – light duty

CONSTRUCTION

PVC tube with rigid PVC helix

SERVICE TEMPERATURE RANGE

-4°F (-20°C) to +150°F (+65°C)*

**Actual service temperature range is application dependent.*

View Up To Date Info



◀ SCAN OR VISIT
**KOA.link/
GTG**



MADE IN THE
USA



FEATURES AND ADVANTAGES

- **Easy Slide Helix** – Rigid helix design protects hose tube from cover wear, and allows hose to slide easily over rough surfaces. Easy-to-handle.
- **Anti-Microbial Tube** – Inhibits growth of bacteria, fungi, mold and yeast.

Series Number	ID		OD		Working Pressure (psi)		Vacuum Rating Hg (in)		Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	at 68°F	at 104°F	at 68°F	at 104°F			
GTG150	1 1/2	38.1	1.82	46.2	20	7	22	14	1	100/50	0.23
GTG200	2	50.8	2.39	60.8	15	6	21	12	2	100	0.30
GTG250	2 1/2	63.5	2.89	73.4	10	5	19	10	2	100/50	0.39
GTG300	3	76.2	3.46	87.9	10	5	18	10	3	100/50	0.50

NOTES:

- Service life may vary depending on operating conditions and type of material being conveyed.

COMPLIANCES (for details see page 87)

Phthalate Free (10), RoHS (11)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.