



WOR™ Series

Standard-Duty, Oil Resistant, PVC Suction Hose

GENERAL APPLICATIONS

- Environmental clean-up
- Oil skimming
- Oil slurries
- Oil suction
- Vapor recovery – hydrocarbon emissions

CONSTRUCTION

Oil resistant PVC tube with rigid PVC helix

SERVICE TEMPERATURE RANGE

5°F (-15°C) to +150°F (+65°C)*

**Actual service temperature range is application dependent.*

View Up To Date Info



◀ SCAN OR VISIT
**KOA.link/
WOR**



FEATURES AND ADVANTAGES

- **Oil Resistant PVC** – Made with special oil resistant compounds which exhibit medium resistance to oil and other hydrocarbons.
- **Convuluted Outer Cover** – Provides increased hose flexibility.

| Series Number | ID | | OD | | Working Pressure (psi) | | Vacuum Rating Hg (in) | | Min. Bending Radius (in) at 68°F | Standard Length (ft) | Weight (lbs/ft) |
|---------------|-------|-------|------|-------|------------------------|----------|-----------------------|----------|----------------------------------|----------------------|-----------------|
| | (in) | (mm) | (in) | (mm) | at 68°F | at 104°F | at 68°F | at 104°F | | | |
| WOR150 | 1 1/2 | 38.1 | 1.92 | 48.8 | 50 | 25 | 28 | 24 | 3 | 100 | 0.31 |
| WOR200 | 2 | 50.8 | 2.40 | 61.0 | 40 | 20 | 28 | 24 | 4 | 100 | 0.50 |
| WOR300 | 3 | 76.2 | 3.64 | 92.5 | 40 | 20 | 28 | 24 | 6 | 100 | 1.17 |
| WOR400 | 4 | 101.6 | 4.72 | 119.9 | 35 | 18 | 28 | 22 | 10 | 100 | 1.74 |

NOTES:

- Service life may vary depending on operating conditions and type of material being conveyed.
- Chemical Resistant Guides (for details see pages 108-109)

COMPLIANCES (for details see page 87)
Phthalate Free (10), **RoHS** (11)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.