

Full Flow Swivel Coupling

Fits hoses: MULCH, MULCH-LT, BARK, LK and UV1


GENERAL APPLICATIONS

Kuriyama Camlock Couplings are intended for use in many industrial Market Applications. To learn more, please visit KOA.link/ff-uses or refer to pages 296-297 in the KOA Couplings & Accessories catalog.

FEATURES AND ADVANTAGES

- **Full Flow Interior** – Prevents material build-up due to the absence of an interior hose shank. Instead, our coupling screws easily and securely over the outside of the hose to provide full flow.
- **Swivel Joint** – Stainless steel ball bearings ensure smooth swivel action, reducing instances of hose twisting.
- **Versatile 2-piece Design** – Coupling consists of male and female ends connected by NPSM threads. Male portion also sold separately.

View Up To Date Info



◀ SCAN OR VISIT
[KOA.link/
Full-Flow](http://KOA.link/Full-Flow)



AL-MHS Series
Full-Flow Swivel
Coupling Set
(Aluminum)



AL-MHM Series
Part D Coupler x
Female
(Aluminum)



AL-MHF Series
Full-Flow Coupling
Female
(Aluminum)



AL-MHD Series
Full-Flow Coupling
Male
(Aluminum)



AL-MHA Series
Part A Male
Coupler x Female
(Aluminum)



*Fits the following
Tigerflex™ series hoses:*

- MULCH™
 - MULCH-LT™
 - BARK™
- LK™
 - UV1™



*Male portion also
sold separately,
connects to
female thread
(NPSM) quick
acting couplings.*

Part Number	Size (in)	Thread Type	Weight Each (lbs)	Standard Carton
AL-MHS400	4	NPSM	2.67	1
AL-MHM400	4	NPSM	0.93	1
AL-MHF400	4	NPSM	1.23	1
AL-MHD400	4	NPSM	2.16	1
AL-MHA400	4	NPSM	1.58	1

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.