



Smooth cover for sizes 10-16



Wrapped cover for size 20



Wrapped cover for sizes 24-32

VIEW ONLINE



SCAN FOR INFO

or visit

KOA.link/E5K



alfabiotech Evolution E5K Series

5000 PSI Minetuff Hydraulic Hose



GENERAL APPLICATIONS

Developed to withstand very demanding conditions very high performance in pressure, pulsing and flexing

CONSTRUCTION

Tube: Oil and biodegradeable hydraulic fluid resistant synthetic rubber Reinforcement: Four/six high tensile steel spirals

Cover: Smooth up to 1", Wrapped over 1", abrasion, ozone and hydrocarbon resistant synthetic rubber

SERVICE TEMPERATURE RANGE

-40°F (-40°C) to +250°F (+121°C)

BRANDING

ALFAGOMMA ALFABIOTECH EVOLUTION 5K MINETUFF ... WP 35 MPa (5000 PSI) - ISO 18752/CC - MSHA IC-152/16 - MADE IN ITALY

LENGTH

Random up to 1" - 200 feet from 1 1/4" to 1 1/2" - 100 feet from 2"

COMPLIANCE DETAILS

Comp	oliances	Size			
DIN	EN856 4SP	5/8", 3/4" and 1"			
DIN	EN856 4SH	1 1/4"			
INTERNATIONAL.	SAE 100R13	All sizes			
ISO	ISO 18752/CC 1,000,000+ impulse cycles	All sizes			
MSHA	MSHA IC-152/16 approved flame resistance	All sizes			

Series Number	Size Code				May Working					Coupling Recommendations				
		ID		OD		Max. Working Pressure	Min. Bend. Radius		Weight	∆lfaCrim n		Two-Piece		
		(in)	(mm)	(in)	(mm)	at 68°F (psi)	(in)	(mm)	(lbs/ft)	AlfaCrimp One-Piece		Ferrule Skive		rule rlock
E5K	10	5/8	15.9	1.00	25.4	5000	3.94	100.0	0.57	S		AS4		
E5K	12	3/4	19.1	1.16	29.4	5000	4.72	120.0	0.79	S	F	AS4	XF2	YS2
E5K	16	1	25.4	1.47	37.4	5000	5.91	150.0	1.10	S	F	AS4	XF2	YS2
E5K	20	1 1/4	31.8	1.73	44.0	5000	8.27	210.0	1.49	S	F		XF2	YS2
E5K	24	1 1/2	38.1	2.16	54.8	5000	9.84	250.0	2.64	S	F			
E5K	32	2	50.8	2.70	68.7	5000	12.52	318.0	3.89	S	F			

[†] Minimum burst pressure 4-to-1 safety factor.

Freight: Hydraulic Hose can be combined with other KOA products for qualifying prepaid freight orders.

