



Kuriyama of America, Inc.
 150 N MARTINGALE ROAD
 SCHAUMBURG, IL 60173-5335 USA
Phone: (847) 755-0360
Toll-Free FAX: (800) 800-0320
International FAX: (847) 885-0996 **Email:** sales@kuriyama.com

Series Number T253AA600X50, T253AA - 6 in. ID and 50 ft Length 150 PSI EPDM Layflat Water Discharge Hose



[General Applications](#) | [Construction](#) | [Working Pressure](#) | [Temperature Range](#) | [Branding](#) | [Nominal Specifications](#) | [Standard Length](#) | [Specifications](#) | [Coupling Suggestions](#) | [Note](#)

General Applications -

GENERAL APPLICATIONS

High pressure, 150 PSI lay flat type hose for general industrial construction and irrigation

Construction -

Tube

Black EPDM.

Reinforcement

High tensile textile cords - 2 spirals up to 4" , 4 spirals above 4"

Cover

Black EPDM - abrasion and ozone resistant.

Working Pressure -

Working Pressure

Constant Pressure - 10 Bar (150 PSI)

Temperature Range

Temperature Range [Min]	-22 °F -30 °C
Temperature Range [Max]	176 °F 80 °C

Branding

Branding	ALFAGOMMA – ITALY – 253 10 BAR (150 PSI) EPDM WATER DISCHARGE (in green letters)
-----------------	--

Nominal Specifications

ID	6 in 152 mm
OD	6.38 in 162 mm
Max. Working Pressure	10 bar 150 psi
Weight	2.00 lbs/ft

Standard Length

Standard Length	50 ft
------------------------	-------

Specifications

Brand	Alfagomma®
Series	T253AA
Type	Water Discharge Hose

Style EPDM Layflat Hose

Color Black

Coupling Suggestions -

Coupling Suggestions

Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

Note -

Note

Kuriyama offers a full line of Quick-Acting couplings, pin lug shank couplings and combination nipples. Refer to current Kuriyama-Couplings™ and Accessories Catalog for type - KOA.link/KOA-Couplings-Catalog