



**Kuriyama of America, Inc.**  
 150 N MARTINGALE ROAD  
 SCHAUMBURG, IL 60173-5335 USA  
**Phone:** (847) 755-0360  
**Toll-Free FAX:** (800) 800-0320  
**International FAX:** (847) 885-0996 **Email:** [sales@kuriyama.com](mailto:sales@kuriyama.com)

## Tiger™ Green TG™ Series EPDM Suction Hose

Made In the USA



1

<u>Series Number</u>	<u>ID</u>	<u>OD</u>	<u>Working Pressure at 68°F</u>	<u>Working Pressure at 104°F</u>	<u>Vacuum Rating at 68°F</u>	<u>Vacuum Rating at 104°F</u>	<u>Min. Bending Radius at 68°F</u>	<u>Standard Length</u>	<u>Weight</u>
<u>TG100X100</u>	1 in 25.4 mm	1.40 in 35.5 mm	65 psi	45 psi	Full	28 inHg	2.0 in	100 ft	0.28 lbs/ft
<u>TG125X100</u>	1 1/4 in 31.8 mm	1.63 in 41.4 mm	60 psi	40 psi	Full	28 inHg	3.0 in	100 ft	0.33 lbs/ft
<u>TG150X100</u>	1 1/2 in 38.1 mm	1.93 in 49.0 mm	50 psi	35 psi	Full	28 inHg	3.0 in	100 ft	0.44 lbs/ft

<u>Series Number</u>	<u>ID</u>	<u>OD</u>	<u>Working Pressure at 68°F</u>	<u>Working Pressure at 104°F</u>	<u>Vacuum Rating at 68°F</u>	<u>Vacuum Rating at 104°F</u>	<u>Min. Bending Radius at 68°F</u>	<u>Standard Length</u>	<u>Weight</u>
<u>TG200X100</u>	2 in 50.8 mm	2.51 in 63.8 mm	50 psi	35 psi	Full	28 inHg	5 in	100 ft	0.67 lbs/ft
<u>TG250X100</u>	2 1/2 in 63.5 mm	3.07 in 78.0 mm	45 psi	30 psi	Full	28 inHg	5 1/2 in	100 ft	0.95 lbs/ft
<u>TG300X100</u>	3 in 76.2 mm	3.60 in 91.5 mm	45 psi	30 psi	Full	26 inHg	7 in	100 ft	1.14 lbs/ft
<u>TG400X100</u>	4 in 101.6 mm	4.70 in 119.5 mm	40 psi	25 psi	Full	26 inHg	11 1/2 in	100 ft	1.84 lbs/ft
<u>TG600X100</u>	6 in 152.4 mm	6.85 in 174.0 mm	30 psi	20 psi	28 inHg	24 inHg	20 in	100 ft	3.07 lbs/ft
<u>TG600X20</u>	6 in 152.4 mm	6.85 in 174.0 mm	30 psi	20 psi	28 inHg	24 inHg	20 in	20 ft	3.07 lbs/ft